

Precision Engineered Recessed Luminaires

ORION



Voltage: 12V
Construction: 316 Marine Grade Stainless Steel
Weight: 3.00 lbs
Socket: Ceramic MR16 Socket
Wattage: Maximum 10 Watts
Lens: High Tempered, Clear Flat 1/8" Glass
Mounting: Recessed or Inground Plastic Sleeve
Lamp Not Included



Recommended LED Lamps

LED 6W VWW 15 SP	6W MR16 2700K 15° Spot
LED 6W VWW 45 FL	6W MR16 2700K 45° Flood
LED 6W WW 15 SP	6W MR16 3000K 15° Spot
LED 6W WW 30 NFL	6W MR16 3000K 30° Narrow Flood
LED 6W WW 45 FL	6W MR16 3000K 45° Flood
LED 6W NW 15 SP	6W MR16 4000K 15° Spot
LED 6W NW 45 FL	6W MR16 4000K 45° Flood
LED 6W CW 15 SP	6W MR16 5500K 15° Spot
LED 6W CW 45 FL	6W MR16 5500K 45° Flood
LED 2X WW 15 SP	2X MR16 3000K 15° Spot
LED 2X WW 30 NFL	2X MR16 3000K 30° Narrow Flood
LED 2X WW 45 FL	2X MR16 3000K 45° Flood

